

**TRANE XV**

MFR DATE 9/2015

MOD.NO. 4TWW0060A1000AC  
SERIAL NO. XXXXXXXXXVOLTS 208/230  
PH 1 HZ 60

MINIMUM CIRCUIT AMPACITY	37.0	AMPS
OVERCURRENT PROTECTIVE DEVICE	USA	CANADA
MAX FUSE / BREAKER (HACR)	50	50
HFC - 410A	11 LBS. 14 OZ. OR	5.38 kg(SI)

10 +/- 3 °F DESIGN SUBCOOLING  
 Climatuff Duratuff Spine Fin Quick-Sess

**TRANE**

HEATING AND COOLING EQUIPMENT

A BUSINESS OF INGERSOLL RAND  
TYLER, TX 75707 ASSEMBLED IN USA

Intertek

3059934

COMPR. MOT.	27.5	RLA	208/230	V	12.0	LRA
O.D MOT.	2.80	FLA	208/230	V	1/3	HP
DESIGN PSI - HIGH	480 LOW 480		F. ID. XXX			

**AHRI** CERTIFIED™  
[www.ahridirectory.org](http://www.ahridirectory.org)

Unitary Small AC  
 AHRI Standard 210/240

Certification applies only when the complete system is listed with AHRI.

**BARCODE**