

**TRANE XR**MFR 1/2023
DATE

MOD. NO. 4TWR6036N1000AA	VOLTS	208/230
SERIAL NO. XXXXXXXXX	PH	1 HZ 60
MINIMUM CIRCUIT AMPACITY	20.0	AMPS
OVERCURRENT PROTECTIVE DEVICE	USA	CANADA
MAX FUSE / BREAKER (HACR)	35	35
HFC - 410A	10 LBS.	15 OZ. OR 4.96 kg(SI)

9 °F SC (TXV) OR SEE SH CHART IN LITERATURE SCCR 5kA rm s
 Climatuff Duratuff Spine Fin Quick-Sess Weathertron

TRANECONDENSING UNIT
SA11679Trane U.S Inc.
TYLER, TX 75707**ASSEMBLED IN USA**

OUTDOOR USE

COMPR. MOT.	15.3 RLA	208/230 V	83 LRA
O.D MOT.	0.77 FLA	200/230 V	1/8 HP
DESIGN PSI - HIGH 480 LOW 480		F. ID. XXX	


AHRI CERTIFIED™
www.ahridirectory.org
Unitary Small AC
AHRI Standard 210/240Certification applies only when the complete system
is listed with AHRI.**BARCODE****QR
CODE**