

**TRANE XR**MFR  
DATE 7/2021

MOD. NO. <b>4TWR4030G1000AB</b>	VOLTS	<b>208/230</b>
SERIAL NO. <b>XXXXXXXXXX</b>	PH <b>1</b>	HZ <b>60</b>
MINIMUM CIRCUIT AMPACITY	<b>17.0</b>	AMPS
OVERCURRENT PROTECTIVE DEVICE	USA	CANADA
MAX FUSE / BREAKER (HACR)	<b>25</b>	<b>25</b>
<b>HFC - 410A</b>	<b>6 LBS. 13 OZ. OR</b>	<b>3.09 kg(SI)</b>
<b>8 °F SC (TXV) OR SEE SH CHART IN LITERATURE</b>		SCCR 5kA rms
Climatuff DuraTuff Spine Fin Quick-Sess Weathertron		

**TRANE**Trane U.S Inc.  
TYLER, TX 75707**ASSEMBLED IN USA**CONDENSING UNIT  
SA11679

OUTDOOR USE

COMPR. MOT.	<b>12.8</b>	RLA	<b>208/230 V</b>	<b>67.8</b>	LRA
O.D MOT.	<b>0.71</b>	FLA	<b>200/230 V</b>	<b>1/8</b>	HP
DESIGN PSI - HIGH 480 LOW 480			F. ID. <b>TWS</b>		

**AHRI CERTIFIED™**  
[www.ahridirectory.org](http://www.ahridirectory.org)Unitary Small AC  
AHRI Standard 210/240Certification applies only when the complete system  
is listed with AHRI.**BARCODE****QR  
CODE**