

HEAT PUMP 13

MFR
DATE 2/2014

MOD. NO. 4TWB3042B1000CA	VOLTS	208/230
SERIAL NO. XXXXXXXXXX	PH 1	HZ 60
MINIMUM CIRCUIT AMPACITY	26.0	AMPS
OVERCURRENT PROTECTIVE DEVICE	USA	CANADA
MAX FUSE / BREAKER (HACR)	45	45
HFC - 410A	7 LBS.	07 OZ. OR 3.38 kg(SI)

8 +/- 3 °F DESIGN SUBCOOLING
Climatuff Duratuff Spine Fin Quick-Sess Weathertron

Trane and American Standard



LISTED SECTION OF
HEAT PUMP

A BUSINESS OF INGERSOLL RAND
TYLER, TX 75707 ASSEMBLED IN USA

3059934 OUTDOOR USE

COMPR. MOT. 19.9 RLA	208/230 V	109	LRA
O.D MOT. 0.97 FLA	200/230 V	1/5	HP
M.E.A. NO.	F. ID. XXX		
DESIGN PSI - HIGH 480 LOW 480			

AHRI CERTIFIED™
www.ahridirectory.org

Unitary Small AC
AHRI Standard 210/240

Certification applies only when the complete system
is listed with AHRI.

BARCODE

Ingersoll Rand