

American Standard

MFR
DATE 1/2010

MOD.NO. 4A7C3042A4000BA	VOLTS	460
SERIAL NO. XXXXXXXXXX	PH 3	HZ 60
MINIMUM CIRCUIT AMPACITY	9.0	AMPS
OVERCURRENT PROTECTIVE DEVICE	USA	CANADA
MAX FUSE / BREAKER (HACR)	15	15
HFC - 410A 7 LBS. 00 OZ.	OR	3.18 kg(SI)
13 °F DESIGN SUBCOOLING		

Climatuff DuraTuff Spine Fin Quick - Sess

TRANE U.S. INC.
MANUFACTURER OF TRANE AND AMERICAN STANDARD
TYLER, TX 75707 ASSEMBLED IN USA



LIMITED SECTION OF
CENTRAL COOLING
AIR CONDITIONER

OUTDOOR USE

COMPR. MOT.	6.4 RLA	460	V	39	LRA
O.D MOT.	.60 FLA	460	V	1/5	HP
M.E.A. NO.		F. ID.	XXX		
DESIGN PSI - HIGH 480 LOW 480					



ARI Standard 210/240
Unitary Heat Pumps

BARCODE

CERTIFICATION APPLIES ONLY
WHEN THE COMPLETE SYSTEM
IS LABELED WITH ARI