

XL 14i

MFR
DATE 1/2005

MOD.NO. 2TWX4060B1000AA	VOLTS	208/230
SERIAL NO. XXXXXXXXXX	PH 1	HZ 60
MINIMUM CIRCUIT AMPACITY	34.0	AMPS
OVERCURRENT PROTECTIVE DEVICE	USA	CANADA
MIN FUSE / BREAKER (HACR)	50	50
MAX FUSE / BREAKER (HACR)	50	50

HCFC - 22 11 LBS. 12 OZ. OR 5.33 kg(SI)
BAYFCCV REQUIRED INDOORS FOR RATED PERFORMANCE

Climatuff DuraTuff Spine Fin Quick - Sess Weathertron

TRANE, A BUSINESS OF
AMERICAN STANDARD

LISTED SECTION OF
HEAT PUMP

TYLER, TX 75707 ASSEMBLED IN USA



23MF OUTDOOR USE

COMPR. MOT.	25.0	RLA	208/230	V	148	LRA
O.D MOT.	2.80	FLA	200/230	V	1/3	HP
M.E.A. NO.			F. ID.	XXX		

DESIGN PSI - HIGH 300 LOW 300



BARCODE

CERTIFICATION APPLIES
ONLY WHEN THE COMPLETE
SYSTEM IS LISTED WITH ARI