

DAIKIN COMFORT TECHNOLOGIES MANUFACTURING, L.P.
19001 KERMIER RD, WALLER, TX 77484

MODEL GSXM401810AB SERIAL NO. XXXXXXXXXX

A.C VOLTS 208-230 PHASE 1 HERTZ 60

VOLTAGE RANGE MIN 197~ MAX. 253~

MAX. FUSE AMPS OR MAX CIRCUIT BREAKER 20

(TIME DELAY FUSE OR HACR CIRCUIT BREAKER REQUIRED)

MIN. CIRCUIT AMPS. 12.0

FAN MOTOR FLA 0.7 H.P 1/8

COMPRESSOR RLA 9.0 LRA 42.6

SHORT-CIRCUIT CURRENT: 5kA RMS SYMMETRICAL, 600V ~ MAXIMUM

MAXIMUM ALLOWABLE PRESSURE PSIG 950

[MPa] 6.55

FACTORY CHARGE OZ. (KG) R-410A 64 (1.8)

TEST PRESSURE PSIG 450

[MPa] 3.1



Intertek
5004994

CR CODE

USE COPPER CONDUCTORS ONLY.
THIS EQUIPMENT SUITABLE FOR OUTDOOR USE.



2024

⚠ WARNING

DISCONNECT ALL ELECTRICAL POWER BEFORE SERVICING.

⚠ ADVERTISSEMENT

COUPEZ TOUT LE COURANT AVANT TOUT ENTRETIEN OU REPARATION.

⚠ ADVERTENCIA

DESCONECTE TODAS LAS FUENTES DE ENERGÍA ELÉCTRICAS ANTES DE MANTENIMIENTO O SERVICIO TÉCNICO.

IP RATING: **IPX4**

PART NO. **SR3R01371**

SR207

PATENTS 8033018 AND 8037595