

**TRANE XR**MFR
DATE 1/2019

MOD.NO. 4TWA4060A3000AA	VOLTS	208/230
SERIAL NO. XXXXXXXXXX	PH 3	HZ 60
MINIMUM CIRCUIT AMPACITY	21.0	AMPS
OVERCURRENT PROTECTIVE DEVICE	USA	CANADA
MAX FUSE / BREAKER (HACR)	35	35
HFC - 410A	10 LBS. 09 OZ. OR	4.78 kg(SI)
8 +/- 3 °F DESIGN SUBCOOLING		SCCR 5kA rms
Climatuff Duratuff Spine Fin Quick-Sess Weathertron		

TRANEHEATING AND COOLING
EQUIPMENTA BUSINESS OF INGERSOLL RAND
TYLER, TX 75707 ASSEMBLED IN USA

Intertek

3059934

COMPR. MOT.	15.9	RLA	208/230 V	110	LRA
O.D MOT.	1.10	FLA	200/230 V	1/5	HP
DESIGN PSI - HIGH 480 LOW 480			F. ID. EBS		

AHRI CERTIFIED™
www.ahridirectory.orgUnitary Small AC
AHRI Standard 210/240Certification applies only when the complete system
is listed with AHRI.**BARCODE**

Ingersoll-Rand