

**TRANE XR**MFR
DATE **6/2022**MOD.NO. **4TTA4036A3000AA**
SERIAL NO. **XXXXXXXXXX**VOLTS **208/230**
PH **3** HZ **60**MINIMUM CIRCUIT AMPACITY **12.0** AMPS
OVERCURRENT PROTECTIVE DEVICE USA CANADA
MAX FUSE / BREAKER (HACR) **20** **20**
HFC - 410A **5** LBS. **08** OZ. OR **2.49** kg(SI)**10 °F SC (TXV) OR SEE SH CHART IN LITERATURE SCCR 5kA rm 8**
Climatuff Duratuff Spine Fin Quick-Sess**TRANE**CONDENSING UNIT
SA11679Trane U.S. Inc.
TYLER, TX 75707

ASSEMBLED IN USA

OUTDOOR USE

COMPR. MOT. **9.0** RLA **208/230** V **71** LRA
O.D MOT. **0.77** FLA **200/230** V **1/8** HP
DESIGN PSI - HIGH 480 LOW 480 F. ID. **DUR****AHRI** CERTIFIED™
www.ahridirectory.orgUnitary Small AC
AHRI Standard 210/240Certification applies only when the complete system
is listed with AHRI.**BARCODE**QR
CODE