

XB 13

MFR
DATE 1/2011

MOD.NO. 4TWB3036A1000BB	VOLTS	208/230
SERIAL NO. XXXXXXXXXX	PH 1	HZ 60
MINIMUM CIRCUIT AMPACITY	21.0	AMPS
OVERCURRENT PROTECTIVE DEVICE	USA	CANADA
MAX FUSE / BREAKER (HACR)	35	35
HFC - 410A	8 LBS. 15 OZ.	OR 3.59 kg(SI)
10 3 +/- °F DESIGN SUBCOOLING		
Climatuff DuraTuff Spine Fin Quick - Sess Weathertron		

TRANE U.S. INC.
MANUFACTURER OF TRANE AND AMERICAN STANDARD



LIMITED SECTION OF
HEAT PUMP

TYLER, TX 75707 ASSEMBLED IN USA

3059934 OUTDOOR USE

COMPR. MOT. 15.4 R/LA	208/230 V	83 LRA
O.D MOT. 1.30 FLA	200/230 V	1/6 HP
M.E.A. NO.	F. ID. XXX	
DESIGN PSI - HIGH 480 LOW 480		

AHRI CERTIFIED™
www.ahridirectory.org

Unitary Small AC
AHRI Standard 210/240

Certification applies only when the complete system
is listed with AHRI.

BARCODE