

**TRANE™**MFR DATE
4/2025

MOD.NO. 5TTR4048A1000AA	VOLTS	208 - 230
SERIAL NO. XXXXXXXXX	PH ~ 1	HZ 60
MINIMUM CIRCUIT AMPACITY	23.0	AMPS
OVERCURRENT PROTECTIVE DEVICE	USA	CANADA
MAX FUSE / BREAKER (HACR)	35	35
R454B - A2L	6 LBS. 10	OZ. OR 2.15 kg(SI)
9°F/6°C	SC (TXV) OR SEE SH CHART IN LITERATURE Climatuff DuraTuff Spine Fin Quick-Sess	SCCR 5kA rms

TRANECONDENSING UNIT
23MFTrane U.S. Inc.
TYLER, TX 75707

ASSEMBLED IN USA



FOR OUTDOOR USE

COMPR. MOT. 16.6	RLA	208 - 230 V	126	LRA
O.D MOT. 0.93	FLA	208 - 230 V	1/5	HP
(PSI/MPA) MAX: 600/4.1 TEST: 450/3.1				F. ID. AV5

AHRI CERTIFIED™
www.ahridirectory.orgUnitary Small AC
AHRI Standard 210/240Certification applies only when the complete system
is listed with AHRI.**BARCODE**QR
CODE