

Allegiance 13

MFR
DATE 7/2007

MOD.NO. 2A7A3030A1000AA	VOLTS	200/230
SERIAL NO. XXXXXXXXX	PH 1	HZ 60
MINIMUM CIRCUIT AMPACITY	13.0	AMPS
OVERCURRENT PROTECTIVE DEVICE	USA	CANADA
MIN FUSE / BREAKER (HACR)	20	20
MAX FUSE / BREAKER (HACR)	20	20

HCFC - 22 5 LBS. 08 OZ. OR 2.49 kg(SI)
10 °F DESIGN SUBCOOLING

Climatuff DuraTuff Spine Fin Quick - Sess

TRANE U.S INC.

MANUFACTURER OF TRANE AND AMERICAN STANDARD

TYLER, TX 75707

ASSEMBLED IN USA



LISTED SECTION OF
CENTRAL COOLING
AIR CONDITIONER
23MF OUTDOOR USE

COMPR. MOT.	9.5	RLA	200/230	V	63	LRA
O.D MOT.	.70	FLA	200/230	V	1/8	HP
M.E.A. NO.	154	O6E	F. ID.	XXX		
DESIGN PSI	- HIGH 300 LOW 300					



BARCODE

CERTIFICATION APPLIES
ONLY WHEN THE COMPLETE
SYSTEM IS LISTED WITH ARI