

# ***XB 1000***

MFR  
DATE **11/99**

MOD.NO. <b>TTB024C100A2</b>	VOLTS	<b>208/230</b>
SERIAL NO. <b>XXXXXXXXXX</b>	PH <b>1</b>	HZ <b>60</b>
MINIMUM CIRCUIT AMPACITY		<b>15.0</b> AMPS
<b>OVERCURRENT PROTECTIVE DEVICE</b>	USA	CANADA
MIN FUSE / BREAKER (HACR)	<b>20</b>	<b>20</b>
MAX FUSE / BREAKER (HACR)	<b>25</b>	<b>25</b>
HCFC - 22 <b>3</b> LBS. <b>06</b> OZ.	OR	<b>1.53</b> kg(al)
BAYFCCV <b>057A</b>	REQUIRED INDOORS FOR RATED PERFORMANCE	

THE TRANE COMPANY  
TYLER, TX 75711-9010 MADE IN USA



OUTDOOR USE

COMPR. MOT. <b>11.6</b> RLA	<b>200/230</b> V	<b>45</b> LRA
O.D MOT. <b>.96</b> FLA	<b>200/230</b> V	<b>1/6</b> HP
M.E.A. NO. <b>58-97E</b>		
DESIGN PSI - HIGH 300 LOW 300		F. ID. <b>L36</b>