

**TRANE XV**MFR
DATE 9/2018

MOD.NO. 4TWV0036A1000BB	VOLTS	208/230
SERIAL NO. XXXXXXXXX	PH 1	HZ 60
MINIMUM CIRCUIT AMPACITY	26.0	AMPS
OVERCURRENT PROTECTIVE DEVICE	USA	CANADA
MAX FUSE / BREAKER (HACR)	40	40
HFC - 410A	9 LBS. 01 OZ. OR	4.31 kg(SI)

9 +/- 3°F DESIGN SUBCOOLING

Climatuff DuraTuff Spine Fin Quick-Sess Weathertron

TRANEHEATING AND COOLING
EQUIPMENT

A BUSINESS OF INGERSOLL RAND

TYLER, TX 75707

ASSEMBLED IN USA

Intertek

3059934

COMPR. MOT. 18.4	RLA	208/230 V	10.2	LRA
O.D MOT. 2.80	FLA	208/230 V	1/3	HP
DESIGN PSI - HIGH 480 LOW 480		F. ID. FGS		

AHRI**CERTIFIED™**www.ahridirectory.orgUnitary Small AC
AHRI Standard 210/240Certification applies only when the complete system
is listed with AHRI.**BARCODE** **Ingersoll Rand**