

Allegiance 13

MFR
DATE 3/2009

MOD.NO. 4A7A3030A1000AA	VOLTS	200/230
SERIAL NO. XXXXXXXXX	PH 1	HZ 60
MINIMUM CIRCUIT AMPACITY	15.0	AMPS
OVERCURRENT PROTECTIVE DEVICE	USA	CANADA
MIN FUSE / BREAKER (HACR)	20	20
MAX FUSE / BREAKER (HACR)	25	25

HFC - 410A 5 LBS. 11 OZ. OR 2.58 kg(SI)

10 °F DESIGN SUBCOOLING

Climatuff DuraTuff Spine Fin Quick - Sess

TRANE U.S INC.

MANUFACTURER OF TRANE AND AMERICAN STANDARD



LISTED SECTION OF
CENTRAL COOLING
AIR CONDITIONER

TYLER, TX 75707

ASSEMBLED IN USA

23MF OUTDOOR USE

COMPR. MOT.	11.1	RLA	200/230	V	63	LRA
O.D MOT.	.70	FLA	200/230	V	1/8	HP
M.E.A. NO.			F. ID.	33P		

DESIGN PSI - HIGH 300 LOW 300



ARI Standard 210/240
Unitary Heat Pumps

BARCODE

CERTIFICATION APPLIES
ONLY WHEN THE COMPLETE
SYSTEM IS LISTED WITH ARI