

# **XB 13**

**MFR**  
**DATE 10/2006**

MOD.NO. <b>2TTA3030A3000AA</b>	VOLTS	<b>200/230</b>
SERIAL NO. <b>XXXXXXXXXX</b>	PH <b>3</b>	HZ <b>60</b>
MINIMUM CIRCUIT AMPACITY	<b>9.0</b>	AMPS
OVERCURRENT PROTECTIVE DEVICE	USA	CANADA
MIN FUSE / BREAKER (HACR)	<b>15</b>	<b>15</b>
MAX FUSE / BREAKER (HACR)	<b>15</b>	<b>15</b>
<b>HFC - 22</b>	<b>5 LBS.</b>	<b>08 OZ.</b>
	OR	<b>2.49 kg(SI)</b>
<b>10 °F DESIGN SUBCOOLING</b>		

**Climatuff DuraTuff Spine Fin Quick - Sess**

**AMERICAN STANDARD INC.**

MANUFACTURER OF TRANE AND AMERICAN STANDARD

TYLER, TX 75707 ASSEMBLED IN USA



LISTED SECTION OF  
CENTRAL COOLING  
AIR CONDITIONER

OUTDOOR USE

COMPR. MOT. <b>6.8</b>	RLA	<b>200/230 V</b>	<b>54.9</b>	LRA
O.D MOT. <b>.70</b>	FLA	<b>200/230 V</b>	<b>1/8</b>	HP
M.E.A. NO.		F. ID. <b>XXX</b>		
DESIGN PSI - HIGH 300 LOW 300				



ARI Standard 210/240  
Unitary Heat Pumps

# **BARCODE**

CERTIFICATION APPLIES ONLY  
WHEN THE COMPLETE SYSTEM  
IS LISTED WITH ARI