

**TRANE****XR 13**MFR 8/2014
DATE

MOD.NO. 4TTR3036E1000AA	VOLTS	208/230
SERIAL NO. XXXXXXXXX	PH 1	HZ 60
MINIMUM CIRCUIT AMPACITY	22.0	AMPS
OVERCURRENT PROTECTIVE DEVICE	USA	CANADA
MAX FUSE / BREAKER (HACR)	35	35

HFC - 410A 6 LBS. 09 OZ. OR 3.37 kg(SI)
 11 +/- 3 °F DESIGN SUBCOOLING

Climatuff DuraTuff Spine Fin Quick - Sess

TRANE,A BUSINESS OF INGERSOLL RAND
TYLER, TX 75707 ASSEMBLED IN USALISTED SECTION OF
CENTRAL COOLING
AIR CONDITIONER
3059934 OUTDOOR USE

COMPR. MOT.	16.7	RLA	208/230	V	79.0	LRA
O.D MOT.	0.64	FLA	200/230	V	1/8	HP
M.E.A. NO.			F. ID. XXX			
DESIGN PSI - HIGH 480 LOW 480						

AHRI CERTIFIED™
www.ahridirectory.orgUnitary Small AC
AHRI Standard 210/240Certification applies only when the complete system
is listed with AHRI.

C

BARCODE