

# XR 13

MFR  
DATE 7/2010

MOD.NO. 4TWR3024A1000AA	VOLTS	200/230
SERIAL NO. XXXXXXXXXX	PH 1	HZ 60
MINIMUM CIRCUIT AMPACITY	12.0	AMPS
OVERCURRENT PROTECTIVE DEVICE	USA	CANADA
MAX FUSE / BREAKER (HACR)	20	20
HFC - 410A 5 LBS. 12 OZ.	OR	2.60 kg(SI)
11 +/- 3° F DESIGN SUBCOOLING		

Climatuff DuraTuff Spine Fin Quick - Sess

TRANE U.S. INC.  
MANUFACTURER OF TRANE AND AMERICAN STANDARD  
TYLER, TX 75707 ASSEMBLED IN USA



LIMITED SECTION OF  
HEAT PUMP

OUTDOOR USE

COMPR. MOT.	9.4	RLA	200/230	V	63	LRA
O.D MOT.	0.70	FLA	200/230	V	1/8	HP
M.E.A. NO.	F. ID. 22Q					
DESIGN PSI - HIGH 480 LOW 480						



ARI Standard 210/240  
Unitary Heat Pumps

## BARCODE

CERTIFICATION APPLIES ONLY  
WHEN THE COMPLETE SYSTEM  
IS LABELED WITH ARI