

**TRANE XR**MFR  
DATE 8/2022MOD. NO. 4TWR5036H1000AC VOLTS 208/230  
SERIAL NO. XXXXXXXXXX PH 1 HZ 60MINIMUM CIRCUIT AMPACITY 18.0 AMPS  
OVERCURRENT PROTECTIVE DEVICE USA CANADA  
MAX FUSE / BREAKER (HACR) 30 30  
HFC - 410A 8 LBS. 05 OZ. OR 3.77 kg(SI)10 °F SC (TXV) OR SEE SH CHART IN LITERATURE SCCR 5kA rm 8  
Climatuff Duratuff Spine Fin Quick-Sess**TRANE**CONDENSING UNIT  
SA11679Trane U.S. Inc.  
TYLER, TX 75707 ASSEMBLED IN USA

OUTDOOR USE

COMPR. MOT. 14.1 RLA 208/230 V 72.2 LRA  
O.D MOT. 0.64 FLA 200/230 V 1/8 HP  
DESIGN PSI - HIGH 480 LOW 480 F. ID. AQU**AHRI** CERTIFIED™  
[www.ahridirectory.org](http://www.ahridirectory.org)Unitary Small AC  
AHRI Standard 210/240Certification applies only when the complete system  
is listed with AHRI.**BARCODE****QR  
CODE**