

# XL 13i

MFR  
DATE 11/2002

MOD. NO. <b>4TWX3042A1000AA</b>	VOLTS	<b>208/230</b>
SERIAL NO. <b>XXXXXXXXXX</b>	PH <b>1</b>	HZ <b>60</b>
MINIMUM CIRCUIT AMPACITY	<b>26.0</b>	AMPS
OVERCURRENT PROTECTIVE DEVICE	USA	CANADA
MIN FUSE / BREAKER (HACR)	<b>40</b>	<b>40</b>
MAX FUSE / BREAKER (HACR)	<b>45</b>	<b>45</b>
HCFC - <b>410A</b>	<b>7 LBS. 05 OZ.</b>	OR <b>3.32 kg(SI)</b>

**BAYFCCV 069A** REQUIRED INDOORS FOR RATED PERFORMANCE

THE TRANE COMPANY  OUTDOOR USE

TYLER, TX 75711-9010 ASSEMBLED IN USA

COMPR. MOT.	<b>19.2</b>	RLA	<b>208/230 V</b>	<b>104</b>	LRA
O.D MOT.	<b>1.90</b>	FLA	<b>200/230 V</b>	<b>1/4</b>	HP
M.E.A. NO.			F. ID.	<b>XXX</b>	

DESIGN PSI - HIGH 480 LOW 480

## BARCODE