

# AIR CONDITIONER

MFR  
DATE 2/2013

MOD.NO. 4TTB4042E1000BA	VOLTS	208/230		
SERIAL NO. XXXXXXXXX	PH 1	HZ 60		
MINIMUM CIRCUIT AMPACITY	23.0	AMPS		
OVERCURRENT PROTECTIVE DEVICE	USA	CANADA		
MAX FUSE / BREAKER (HACR)	40	40		
HFC - 410A	8 LBS.	04 OZ.	OR	3.28 kg(SI)
8 +/- 3 °F DESIGN SUBCOOLING				
Climatuff DuraTuff Spine Fin Quick - Sess				

**TRANE**

A BUSINESS OF INGERSOLL RAND  
TYLER, TX 75707 ASSEMBLED IN USA



LISTED SECTION OF  
CENTRAL COOLING  
AIR CONDITIONER

3059934 OUTDOOR USE

COMPR. MOT.	17.9	RLA	208/230 V	112	LRA
O.D MOT.	0.93	FLA	200/230 V	1/5	HP
M.E.A. NO.	HVAC SUPPLY CO.		F. ID. XXX		
DESIGN PSI - HIGH 480 LOW 480					



**AHRI** CERTIFIED™  
[www.ahridirectory.org](http://www.ahridirectory.org)

Unitary Small AC  
AHRI Standard 210/240

Certification applies only when the complete system  
is listed with AHRI.

C.

# BARCODE

**IR** Ingersoll-Rand