

**TRANE XR**

MFR DATE 1/2017

MOD. NO. 4TWR4030G1000AA
SERIAL NO. XXXXXXXXXVOLTS 208/230
PH 1 HZ 60MINIMUM CIRCUIT AMPACITY
OVERCURRENT PROTECTIVE DEVICE
MAX FUSE / BREAKER (HACR)17.0 AMPS
USA CANADA
25 25

HFC - 410A 6 LBS. 13 OZ. OR 3.12 kg(SI)

8 +/- 3 °F DESIGN SUBCOOLING
Climatuff Duratuff Spine Fin Quick- Sess Weathertron**TRANE**HEATING AND COOLING
EQUIPMENTA BUSINESS OF INGERSOLL RAND
TYLER, TX 75707 ASSEMBLED IN USA

Intertek 3059934

COMPR. MOT. 12.5 RLA 208/230 V 57.8 LRA
O.D MOT. 0.77 FLA 200/230 V 1/8 HP
DESIGN PSI - HIGH 480 LOW 480 F. ID. BSS**AHRI****CERTIFIED™**
www.ahridirectory.orgUnitary Small AC
AHRI Standard 210/240Certification applies only when the complete system
is listed with AHRI.**BARCODE**

Ingersoll-Rand