

XR 12

MFR
DATE 3/2005

MOD.NO. 2TWR2030B1000AA	VOLTS 208/230
SERIAL NO. XXXXXXXXXX	PH 1 HZ 60
MINIMUM CIRCUIT AMPACITY	18.0 AMPS
OVERCURRENT PROTECTIVE DEVICE	USA CANADA
MIN FUSE / BREAKER (HACR)	30 30
MAX FUSE / BREAKER (HACR)	30 30

HCFC - **22** 5 LBS. **08** OZ. OR **2.49** kg(SI)
BAYFCCV **063A** REQUIRED INDOORS FOR RATED PERFORMANCE

Climatuff DuraTuff Spine Fin Quick - Sess Weathertron

TRANE, A BUSINESS OF
AMERICAN STANDARD



LISTED SECTION OF
HEAT PUMP

TYLER, TX 75707 ASSEMBLED IN USA

23MF OUTDOOR USE

COMPR. MOT. 13.5 RLA	208/230 V 73 LRA
O.D MOT. .90 FLA	200/230 V 1/8 HP
M.E.A. NO.	F. ID. K28
DESIGN PSI - HIGH 300 LOW 300	



BARCODE

CERTIFICATION APPLIES
ONLY WHEN THE COMPLETE
SYSTEM IS LISTED WITH ARI