

XR 15

MFR
DATE 5/2010

MOD.NO. 4TTR5036E1000AB	VOLTS	208/230
SERIAL NO. XXXXXXXXX	PH 1	HZ 60
MINIMUM CIRCUIT AMPACITY	19.0	AMPS
OVERCURRENT PROTECTIVE DEVICE	USA	CANADA

MAX FUSE / BREAKER (HACR) **30 30**
HFC - **410A** 7 LBS. 04 OZ. OR **3.28** kg(SI)

11 °F DESIGN SUBCOOLING
Climatuff DuraTuff Spine Fin Quick - Sess

TRANE

MANUFACTURER OF TRANE AND AMERICAN STANDARD



LISTED SECTION OF
CENTRAL COOLING
AIR CONDITIONER

TYLER, TX 75707 ASSEMBLED IN USA

3059934 OUTDOOR USE

COMPR. MOT.	14.1	RLA	208/230 V	77	LRA
O.D MOT.	1.00	FLA	200/230 V	1/5	HP
M.E.A. NO.			F. ID. XXX		
DESIGN PSI - HIGH	480	LOW	480		



CERTIFICATION APPLIES ONLY
WHEN THE COMPLETE SYSTEM
IS LISTED WITH ARI

BARCODE