

XL 14i

MFR
DATE 2/2007

MOD.NO. 4TTX4036B1000AA	VOLTS	208/230
SERIAL NO. XXXXXXXXX	PH 1	HZ 60
MINIMUM CIRCUIT AMPACITY	21.0	AMPS
OVERCURRENT PROTECTIVE DEVICE	USA	CANADA
MIN FUSE / BREAKER (HACR)	30	30
MAX FUSE / BREAKER (HACR)	35	35
HFC - 410A	5 LBS.	11 OZ. OR 2.58 kg(SI)
10 °F DESIGN SUBCOOLING		

Climatuff DuraTuff Spine Fin Quick - Sess Weatherton

AMERICAN STANDARD INC.

MANUFACTURER OF TRANE AND AMERICAN STANDARD

TYLER, TX 75707 ASSEMBLED IN USA



LISTED SECTION OF
CENTRAL COOLING
AIR CONDITIONER

OUTDOOR USE

COMPR. MOT.	15.4	RLA	208/230 V	83	LRA
O.D MOT.	1.40	FLA	200/230 V	1/6	HP
M.E.A. NO.	F. ID. XXX				
DESIGN PSI - HIGH 480 LOW 480					



CERTIFICATION APPLIES ONLY
WHEN THE COMPLETE SYSTEM
IS LISTED WITH ARI

BARCODE