

# Hisense

## PORTABLE AIR CONDITIONER

<b>*SACC</b>	<b>7500 Btu/hr</b>
<b>Cooling Current</b>	<b>10.3 A</b>
<b>Input Cooling Power</b>	<b>1175 W</b>
<b>Power Source</b>	<b>1PH/115V~/60Hz</b>
<b>L.R.A/R.L.A Of Compressor</b>	<b>50.5 A/9.5 A</b>
<b>F.L.A Of Fan Motor(Up/Down)</b>	<b>0.42 A/1.02 A</b>
<b>Rated Current</b>	<b>11.8 A</b>
<b>Refrigerant R410A</b>	<b>16.57 OZ</b>
<b>Circulation Air Flow</b>	<b>230 CFM</b>
<b>Maximum Operating Pressure High</b>	<b>4.14 MPa(600 PSIG)</b>
<b>Low</b>	<b>1.60 MPa(236 PSIG)</b>
<b>Maximum Allowable Pressure</b>	<b>20 MPa(2900 PSIG)</b>



**Intertek**  
3088177

CONFORMS TO  
UL STD.60335-1  
AND 60335-2-40  
CERTIFIED TO  
CSA STD.C22.2  
No.60335-1 AND  
60335-2-40

**MODEL# AP1219CR1W**

Date Manufactured: 1118

**MADE IN CHINA**

\* 10 CFR Part 430, Appendix CC to subpart B