

XV 20MFR
DATE 11/2013

MOD.NO. 4TWV0036A1000AA	VOLTS	208/230
SERIAL NO. XXXXXXXXXX	PH 1	HZ 60
MINIMUM CIRCUIT AMPACITY	26.0	AMPS
OVERCURRENT PROTECTIVE DEVICE	USA	CANADA
MAX FUSE / BREAKER (HACR)	40	40
HFC - 410A	9 LBS.	08 OZ.
	OR	4.31 kg(SI)
9 +/- 3 °F DESIGN SUBCOOLING		
Climatuff DuraTuff Spine Fin Quick - Sess Weathertron		

TRANELISTED SECTION OF
HEAT PUMPA BUSINESS OF INGERSOLL RAND
TYLER, TX 75707 ASSEMBLED IN USA

3059934 OUTDOOR USE

COMPR. MOT.	18.4	RLA	208/230	V	10.2	LRA
O.D MOT.	2.80	FLA	208/230	V	1/3	HP
M.E.A. NO.			F. ID.	UJQ		

DESIGN PSI - HIGH 480 LOW 480

AHRI CERTIFIED™
www.ahridirectory.org

Unitary Small AC
AHRI Standard 210/240Certification applies only when the complete system
is listed with AHRI.

BARCODE