XL 16i

MFR
DATE 5/2012

MOD.NO. **4TWX6048G1000AA**	VOLTS	**208/230**	
SERIAL NO. **XXXXXXXXX**	PH **1**	HZ **60**	
MINIMUM CIRCUIT AMPACITY	**28.0**	AMPS	
OVERCURRENT PROTECTIVE DEVICE	USA	CANADA	
MAX FUSE / BREAKER (HACR)	**45**	**45**	
HFC – 410A	**12** LBS.	**09** OZ. OR	**5.71** kg(SI)

8 +/- 3 °F DESIGN SUBCOOLING

Climatuff DuraTuff Spine Fin Quick-Sess Weathertron

TRANE U.S INC.

MANUFACTURER OF TRANE AND AMERICAN STANDARD

TYLER, TX 75707 **ASSEMBLED IN USA**

INTERTEK ETL LISTED C US

LISTED SECTION OF HEAT PUMP

3059934 OUTDOOR USE

COMPR. MOT.	**23.6**	RLA	**208/230**	V	**104**	LRA
O.D MOT.	**1.00**	FLA	**208/230**	V	**1/5**	HP
M.E.A. NO.			F. ID. **LMQ**			

DESIGN PSI - HIGH 480 LOW 480

MILAND HVAC SUPPLY

energy ENERGY STAR

AHRI CERTIFIED™
www.ahridirectory.org
Unitary Small AC
AHRI Standard 210/240
Certification applies only when the complete system is listed with AHRI.

B A R C O D E

QR CODE