

**TRANE XR**MFR
DATE 10/2018

MOD.NO. 4TWR7048A100AA	VOLTS	208/230
SERIAL NO. XXXXXXXXX	PH 1	HZ 60
MINIMUM CIRCUIT AMPACITY	28.0	AMPS
OVERCURRENT PROTECTIVE DEVICE	USA	CANADA
MAX FUSE / BREAKER (HACR)	45	45
HFC - 410A	12 LBS. 09 OZ.	OR 5.71 kg(SI)
8 +/- 3 °F DESIGN SUBCOOLING		
Climatuff DuraTuff Spine Fin Quick - Sess Weathertron		

TRANEHEATING AND COOLING
EQUIPMENTA BUSINESS OF INGERSOLL RAND
TYLER, TX 75707 ASSEMBLED IN USA

Intertek

3959934

COMPR. MOT.	21.2 RLA	208 - 230 V	104 LRA
O.D MOT.	1.00 FLA	208 - 230 V	1/5 HP
DESIGN PSI - HIGH 480 LOW 480		F. ID. EYS	

AHRI**CERTIFIED™**
www.ahridirectory.orgUnitary Small AC
AHRI Standard 210/240Certification applies only when the complete system
is listed with AHRI.

BARCODE

IR Ingersoll-Rand