

XB 10

MFR
DATE 1/2004

MOD.NO. 2TTB0036A1000AA	VOLTS	200/230
SERIAL NO. XXXXXXXXXX	PH 1	HZ 60
MINIMUM CIRCUIT AMPACITY	20.0	AMPS
OVERCURRENT PROTECTIVE DEVICE	USA	CANADA
MIN FUSE / BREAKER (HACR)	30	30
MAX FUSE / BREAKER (HACR)	35	35

HCFC - 22 **4 LBS. 12 OZ. OR 2.15 kg(SI)**
BAYFCCV 071A REQUIRED INDOORS FOR RATED PERFORMANCE

Climatuff DuraTuff Spine Fin Quick - Sess

TRANE, A BUSINESS OF
AMERICAN STANDARD



LISTED SECTION OF
CENTRAL COOLING
AIR CONDITIONER

TYLER, TX 75707 ASSEMBLED IN USA

23MF OUTDOOR USE

COMPR. MOT. 15.3	RLA	200/230	V	87	LRA
O.D MOT. .90	FLA	200/230	V	1/8	HP
M.E.A. NO.					
DESIGN PSI - HIGH 300	LOW 300	F. ID. XXX			



BARCODE

CERTIFICATION APPLIES
ONLY WHEN THE COMPLETE
SYSTEM IS LISTED WITH ARI