

XR 13

MFR
DATE 2/2009

MOD.NO. 4TTR3030A1000AA	VOLTS	200/230
SERIAL NO. XXXXXXXXX	PH 1	HZ 60
MINIMUM CIRCUIT AMPACITY	15.0	AMPS
OVERCURRENT PROTECTIVE DEVICE	USA	CANADA
MIN FUSE / BREAKER (HACR)	20	20
MAX FUSE / BREAKER (HACR)	25	25
HFC - 410A	5 LBS. 11 OZ.	OR 2.58 kg(SI)
10 °F DESIGN SUBCOOLING		

Climatuff DuraTuff Spine Fin Quick - Sess

TRANE U.S. INC.
MANUFACTURER OF TRANE AND AMERICAN STANDARD
TYLER, TX 75707 ASSEMBLED IN USA



LIMITED SECTION OF
CENTRAL COOLING
AIR CONDITIONER
23MF OUTDOOR USE

COMPR. MOT.	11.1	RLA	200/230 V	63	LRA
O.D MOT.	.70	FLA	200/230 V	1/8	HP
M.E.A. NO.	F. ID. 26P				
DESIGN PSI - HIGH 480 LOW 480					

BARCODE



ARI Standard 210/240TM
Unitary Heat Pumps
ARI Standard
210/240 UAC

CERTIFICATION APPLIES ONLY
WHEN THE COMPLETE SYSTEM
IS LISTED WITH ARI