

# XL 15i

MFR  
DATE 7/2008

MOD.NO. 4TWX5048A100AA	VOLTS	208/230
SERIAL NO. XXXXXXXXX	PH 1	HZ 60
MINIMUM CIRCUIT AMPACITY	30.0	AMPS
OVERCURRENT PROTECTIVE DEVICE	USA	CANADA
MIN FUSE / BREAKER (HACR)	50	50
MAX FUSE / BREAKER (HACR)	50	50
HFC - 410A	12 LBS. 01 OZ. OR	5.47 kg(SI)
10 °F DESIGN SUBCOOLING		

Climatuff DuraTuff Spine Fin Quick - Sess Weathertron

## TRANE U.S. INC.

MANUFACTURER OF TRANE AND AMERICAN STANDARD

TYLER, TX 75707

ASSEMBLED IN USA



LISTED SECTION OF  
HEAT PUMP

23MF OUTDOOR USE

COMPR. MOT.	21.8	RLA	208/230 V	117	LRA
O.D MOT.	2.80	FLA	200/230 V	1/3	HP
M.E.A. NO.	F. ID. 62Q				
DESIGN PSI - HIGH 480 LOW 480					



ARI Standard 210/240  
Unitary Heat Pumps

# BARCODE

CERTIFICATION APPLIES ONLY  
WHEN THE COMPLETE SYSTEM  
IS LISTED WITH ARI