

**TRANE XR**

MFR DATE 2/2023

MOD.NO. 4TTR5042N1000AA	VOLTS	208/230
SERIAL NO. XXXXXXXXX	PH 1	HZ 60
MINIMUM CIRCUIT AMPACITY	21.0	AMPS
OVERCURRENT PROTECTIVE DEVICE	USA	CANADA
MAX FUSE / BREAKER (HACR)	35	35
HFC - 410A	8 LBS. 02 OZ. OR	3.69 kg(SI)

8 °F SC (TXV) OR SEE SH CHART IN LITERATURE SCCR 5kA rm s
 Climatuff Duratuff Spine Fin Quick-Sess

TRANE

CONDENSING UNIT SA11679

Trane U.S Inc.
TYLER, TX 75707**ASSEMBLED IN USA**

OUTDOOR USE

COMPR. MOT.	16.7 RLA	208/230 V	109 LRA
O.D MOT.	0.64 FLA	200/230 V	1/8 HP
DESIGN PSI - HIGH 480	LOW 480	F. ID. C6T	



AHRI CERTIFIED™
www.ahridirectory.org

Unitary Small AC
 AHRI Standard 210/240

Certification applies only when the complete system
 is listed with AHRI.

BARCODE**QR
CODE**