

XL 14i

MFR
DATE 4/2005

MOD.NO. 4TWX4024B1000AA	VOLTS	200/230
SERIAL NO. XXXXXXXXXX	PH 1	HZ 60
MINIMUM CIRCUIT AMPACITY	13.0	AMPS
OVERCURRENT PROTECTIVE DEVICE	USA	CANADA
MIN FUSE / BREAKER (HACR)	20	20
MAX FUSE / BREAKER (HACR)	20	20

HCFC - 410A 6 LBS. 10 OZ. OR 3.01 kg(SI)
BAYFCCV 053A REQUIRED INDOORS FOR RATED PERFORMANCE

Climatuff DuraTuff Spine Fin Quick - Sess Weathertron

TRANE, A BUSINESS OF
AMERICAN STANDARD



LISTED SECTION OF
HEAT PUMP

TYLER, TX 75707 ASSEMBLED IN USA

23MF OUTDOOR USE

COMPR. MOT. 9.4	RLA	200/230	V	63	LRA
O.D MOT. .90	FLA	200/230	V	1/8	HP
M.E.A. NO.		F. ID. XXX			

DESIGN PSI - HIGH 480 LOW 480



BARCODE

CERTIFICATION APPLIES
ONLY WHEN THE COMPLETE
SYSTEM IS LISTED WITH ARI