

**TRANE XR**

MFR DATE 3/2023

MOD.NO. 4TTL5048N1000AA	VOLTS	208/230
SERIAL NO. XXXXXXXXX	PH 1	HZ 60
MINIMUM CIRCUIT AMPACITY	24.0	AMPS
OVERCURRENT PROTECTIVE DEVICE	USA	CANADA
MAX FUSE / BREAKER (HACR)	40	40
HFC - 410A	8 LBS. 05 OZ. OR	3.77 kg(SI)
9 °F SC (TXV) OR SEE SH CHART IN LITERATURE		SCCR 5kA rms
Climatuff DuraTuff Spine Fin Quick-Sess		

TRANECONDENSING UNIT
SA11679Trane U.S. Inc.
TYLER, TX 75707

ASSEMBLED IN USA



OUTDOOR USE

COMPR. MOT. 18.3	RLA	208/230 V	108.0	LRA
O.D. MOT. 1.05	FLA	200/230 V	1/5	HP
DESIGN PSI - HIGH 480 LOW 480	F. ID. GLT			

AHRI CERTIFIED™
www.ahridirectory.orgUnitary Small AC
AHRI Standard 210/240Certification applies only when the complete system
is listed with AHRI.**BARCODE****QR
CODE**