

**TRANE XR**MFR  
DATE 3/2015

MOD.NO. 4TWR4060D1000AA

SERIAL NO. XXXXXXXXX

VOLTS 208/230

PH 1 HZ 60

MINIMUM CIRCUIT AMPACITY

34.0 AMPS

OVERCURRENT PROTECTIVE DEVICE

USA CANADA

MAX FUSE / BREAKER (HACR)

60 60 - MA

HFC - 410A 13 LBS. 12 OZ. OR 6.25 kg(SI)

10 +/- 3 °F DESIGN SUBCOOLING

Climatuff Duratuff Spine Fin Quick-Sess

**TRANE**HEATING AND COOLING  
EQUIPMENT

A BUSINESS OF INGERSOLL RAND

TYLER, TX 75707 ASSEMBLED IN USA

Intertek 3059934

COMPR. MOT. 26.4 RLA 208/230 V 134 LRA

O.D MOT. 1.30 FLA 200/230 V 1/4 HP

DESIGN PSI - HIGH 480 LOW 480 F. ID. WCQ

**AHRI** CERTIFIED™  
[www.ahridirectory.org](http://www.ahridirectory.org)Unitary Small AC  
AHRI Standard 210/240Certification applies only when the complete system  
is listed with AHRI.**BARCODE**

Ingersoll Rand