

**TRANE XR**MFR
DATE 6/2019

MOD. NO. 4TWR4060G1000AA	VOLTS	208/230
SERIAL NO. XXXXXXXXXX	PH 1	HZ 60
MINIMUM CIRCUIT AMPACITY	32.0	AMPS
OVERCURRENT PROTECTIVE DEVICE	USA	CANADA
MAX FUSE / BREAKER (HACR)	50	50
HFC - 410A	9 LBS. 14 OZ. OR	4.48 kg(SI)
10 +/- 3 °F DESIGN SUBCOOLING		SCCR 5kA rms

Climatuff Duratuff Spine Fin Quick-Sess

TRANEHEATING AND COOLING
EQUIPMENT

A BUSINESS OF INGERSOLL RAND

TYLER, TX 75707 ASSEMBLED IN USA

Intertek

3059934

COMPR. MOT.	24.4	RLA	208/230 V	144	LRA
O.D MOT.	1.05	FLA	200/230 V	1/5	HP
DESIGN PSI - HIGH 480 LOW 480			F. ID. BWS		

**AHRI CERTIFIED™**www.ahridirectory.orgUnitary Small AC
AHRI Standard 210/240Certification applies only when the complete system
is listed with AHRI.**BARCODE****Ingersoll-Rand**