

XL 16i

MFR
DATE 3/2007

MOD.NO. 4TWX6048B1000BA	VOLTS	230
SERIAL NO. XXXXXXXXX	PH 1	HZ 60
MINIMUM CIRCUIT AMPACITY	28.0	AMPS
OVERCURRENT PROTECTIVE DEVICE	USA	CANADA
MIN FUSE / BREAKER (HACR)	40	40
MAX FUSE / BREAKER (HACR)	45	45
HFC - 410A	9 LBS.	01 OZ. OR 4.11 kg(SI)
9 °F DESIGN SUBCOOLING		

Climatuff DuraTuff Spine Fin Quick - Sess Weathertron

AMERICAN STANDARD INC.

MANUFACTURER OF TRANE AND AMERICAN STANDARD

TYLER, TX 75707 ASSEMBLED IN USA



LISTED SECTION OF
HEAT PUMP

23MF OUTDOOR USE

COMPR. MOT.	21.2	RLA	230	V	96	LRA
O.D MOT.	1.00	FLA	200/230	V	1/5	HP
M.E.A. NO.						F. ID. 55Q
DESIGN PSI - HIGH 480 LOW 480						



CERTIFICATION APPLIES ONLY
WHEN THE COMPLETE SYSTEM
IS LISTED WITH ARI

BARCODE