

**TRANE XR**MFR 2/2021  
DATE

|                                 |                  |                           |
|---------------------------------|------------------|---------------------------|
| MOD. NO. <b>4TTR4060L1000BA</b> | VOLTS            | <b>208/230</b>            |
| SERIAL NO. <b>XXXXXXXXXX</b>    | PH <b>1</b>      | HZ <b>60</b>              |
| MINIMUM CIRCUIT AMPACITY        | <b>27.0</b>      | AMPS                      |
| OVERCURRENT PROTECTIVE DEVICE   | USA              | CANADA                    |
| MAX FUSE / BREAKER (HACR)       | <b>45</b>        | <b>45</b>                 |
| <b>HFC - 410A</b>               | <b>7 LBS. 10</b> | <b>OZ. OR 3.46 kg(SI)</b> |

**10** °F SC (TXV) OR SEE SH CHART IN LITERATURE SCCR 5KA rms  
Climatuff Duratuff Spine Fin Quick-Sess

**TRANE**Trane U.S Inc.  
TYLER, TX 75707CONDENSING UNIT  
SA11679**ASSEMBLED IN USA**

OUTDOOR USE

|                               |                   |                  |
|-------------------------------|-------------------|------------------|
| COMPR. MOT. <b>18.5</b> RLA   | <b>208/230 V</b>  | <b>127.1</b> LRA |
| O.D MOT. <b>0.93</b> FLA      | <b>200/230 V</b>  | <b>1/5</b> HP    |
| DESIGN PSI - HIGH 480 LOW 480 | F. ID. <b>XXX</b> |                  |

**AHRI CERTIFIED™**  
www.ahridirectory.org

Unitary Small AC  
AHRI Standard 210/240Certification applies only when the complete system  
is listed with AHRI.**BARCODE****QR  
CODE**