

XB 10

MFR
DATE 2/2004

MOD.NO. 2TTB0042A1000AA	VOLTS	200/230
SERIAL NO. XXXXXXXXXX	PH 1	HZ 60
MINIMUM CIRCUIT AMPACITY	23.0	AMPS
OVERCURRENT PROTECTIVE DEVICE	USA	CANADA
MIN FUSE / BREAKER (HACR)	40	40
MAX FUSE / BREAKER (HACR)	40	40

HCFC - 22 5 LBS. 15 OZ. OR 2.69 kg(SI)
BAYFCCV 071A REQUIRED INDOORS FOR RATED PERFORMANCE

Climatuff DuraTuff Spine Fin Quick - Sess

TRANE, A BUSINESS OF
AMERICAN STANDARD



LISTED SECTION OF
CENTRAL COOLING
AIR CONDITIONER

TYLER, TX 75707 ASSEMBLED IN USA

23MF OUTDOOR USE

COMPR. MOT.	17.5	RLA	200/230	V	92	LRA
O.D MOT.	1.30	FLA	200/230	V	1/4	HP
M.E.A. NO.	249 - 02 - E		F. ID.		B55	
DESIGN PSI - HIGH 300 LOW 300						



BARCODE

CERTIFICATION APPLIES
ONLY WHEN THE COMPLETE
SYSTEM IS LISTED WITH ARI