

# **XB 13**

**MFR**  
**DATE 8/2008**

MOD.NO. <b>2TTA3060A3000AA</b>	VOLTS	<b>200/230</b>
SERIAL NO. <b>XXXXXXXXXX</b>	PH <b>3</b>	HZ <b>60</b>
MINIMUM CIRCUIT AMPACITY	<b>23.0</b>	AMPS
OVERCURRENT PROTECTIVE DEVICE	USA	CANADA
MIN FUSE / BREAKER (HACR)	<b>40</b>	<b>40</b>
MAX FUSE / BREAKER (HACR)	<b>40</b>	<b>40</b>
<b>HCFC - 22</b>	<b>8 LBS. 11 OZ.</b>	OR <b>3.94 kg(SI)</b>
<b>10 °F DESIGN SUBCOOLING</b>		

**Climatuff DuraTuff Spine Fin Quick - Sess**

TRANE U.S. INC.  
MANUFACTURER OF TRANE AND AMERICAN STANDARD  
TYLER, TX 75707 ASSEMBLED IN USA



LIMITED SECTION OF  
CENTRAL COOLING  
AIR CONDITIONER  
23MF **OUTDOOR USE**

COMPR. MOT.	<b>17.3</b>	RLA	<b>200/230 V</b>	<b>123</b>	LRA
O.D MOT.	<b>1.30</b>	FLA	<b>200/230 V</b>	<b>1/4</b>	HP
M.E.A. NO.	<b>154 - 06E</b>		F. ID. <b>45N</b>		
DESIGN PSI - HIGH 300 LOW 300					

**BARCODE**



ARI Standard 210/240<sup>TM</sup>  
Unitary Heat Pumps  
ARI Standard  
210/240 UAC

CERTIFICATION APPLIES ONLY  
WHEN THE COMPLETE SYSTEM  
IS LISTED WITH ARI