

XL 15i

MFR
DATE 4/2008

MOD.NO. 4TTX5024A1000AA	VOLTS	200/230
SERIAL NO. XXXXXXXXX	PH 1	HZ 60
MINIMUM CIRCUIT AMPACITY	19.0	AMPS
OVERCURRENT PROTECTIVE DEVICE	USA	CANADA
MIN FUSE / BREAKER (HACR)	20	20
MAX FUSE / BREAKER (HACR)	20	20
HFC - 410A	6 LBS.	10 OZ. OR 3.01 kg(SI)
10 °F DESIGN SUBCOOLING		

Climatuff DuraTuff Spine Fin Quick - Sess

TRANE

MANUFACTURER OF TRANE AND AMERICAN STANDARD

TYLER, TX 75707 ASSEMBLED IN USA



LISTED SECTION OF
CENTRAL COOLING
AIR CONDITIONER

3059934 OUTDOOR USE

COMPR. MOT.	8.6	RLA	200/230 V	57.8	LRA
O.D MOT.	2.80	FLA	200/230 V	1/3	HP
M.E.A. NO.			F. ID. XXX		
DESIGN PSI - HIGH 480 LOW 480					



CERTIFICATION APPLIES ONLY
WHEN THE COMPLETE SYSTEM
IS LISTED WITH ARI

BARCODE