

**TRANE XR**MFR
DATE 11/2017

MOD. NO. 4TWR6018H1000AB	VOLTS	208/230
SERIAL NO. XXXXXXXXXX	PH 1	HZ 60
MINIMUM CIRCUIT AMPACITY	12.0	AMPS
OVERCURRENT PROTECTIVE DEVICE	USA	CANADA
MAX FUSE / BREAKER (HACR)	20	20
HFC - 410A	7 LBS. 04	OZ. OR 3.28 kg(SI)

8 +/- 3 °F DESIGN SUBCOOLING
Climatuff DuraTuff Spine Fin Quick - Sess Weathertron

TRANEHEATING AND COOLING
EQUIPMENTA BUSINESS OF INGERSOLL RAND
TYLER, TX 75707 ASSEMBLED IN USA**Intertek**

3059934

COMPR. MOT. 9.0	RLA	208/230	V	56	LRA
O.D MOT. 0.54	FLA	200/230	V	1/8	HP
DESIGN PSI - HIGH 480	LOW 480	F. ID.	E2S		

AHRI**CERTIFIED™**www.ahridirectory.orgUnitary Small AC
AHRI Standard 210/240Certification applies only when the complete system
is listed with AHRI.

BARCODE

IR Ingersoll Rand