

**TRANE XR**MFR
DATE **6/2017**MOD. NO. **4TTR4048L1000AA**
SERIAL NO. **XXXXXXXXXX**VOLTS **208/230**
PH **1** HZ **60**

MINIMUM CIRCUIT AMPACITY	24.0	AMPS
OVERCURRENT PROTECTIVE DEVICE	USA	CANADA
MAX FUSE / BREAKER (HACR)	40	40
HFC - 410A	6 LBS. 09	0Z. OR 2.98 kg(SI)

10 +/- 3 °F DESIGN SUBCOOLING
 Climatuff Duratuff Spine Fin Quick-Sess

TRANEHEATING AND COOLING
EQUIPMENTA BUSINESS OF INGERSOLL RAND
TYLER, TX 75707 ASSEMBLED IN USA**Intertek**

3059934

COMPR. MOT.	18.5	RLA	208/230 V	124	LRA
O.D MOT.	0.93	FLA	200/230 V	1/5	HP
DESIGN PSI - HIGH	480	LOW	480	F. ID.	WPP

AHRI**CERTIFIED™**www.ahridirectory.orgUnitary Small AC
AHRI Standard 210/240Certification applies only when the complete system
is listed with AHRI.**BARCODE** **Ingersoll Rand**