

XL 16i

MFR
DATE 7/2007

MOD.NO. 4TTX6048B1000BA	VOLTS	230
SERIAL NO. XXXXXXXXX	PH 1	HZ 60
MINIMUM CIRCUIT AMPACITY	28.0	AMPS
OVERCURRENT PROTECTIVE DEVICE	USA	CANADA
MIN FUSE / BREAKER (HACR)	40	40
MAX FUSE / BREAKER (HACR)	45	45
HFC - 410A	7 LBS. 08 OZ. OR	3.40 kg(SI)
12 °F DESIGN SUBCOOLING		

Climatuff DuraTuff Spine Fin Quick - Sess

AMERICAN STANDARD INC.

MANUFACTURER OF TRANE AND AMERICAN STANDARD

TYLER, TX 75707 ASSEMBLED IN USA



LISTED SECTION OF
CENTRAL COOLING
AIR CONDITIONER

23MF OUTDOOR USE

COMPR. MOT.	21.2	RLA	230	V	96	LRA
O.D MOT.	1.00	FLA	200/230	V	1/5	HP
M.E.A. NO.	392 - 04 - E		F. ID. XXX			
DESIGN PSI - HIGH 480 LOW 480						



CERTIFICATION APPLIES ONLY
WHEN THE COMPLETE SYSTEM
IS LISTED WITH ARI

BARCODE