

**TRANE XV**

MFR DATE 10/2015

MOD.NO. 4TTV8036A1000AC  
SERIAL NO. XXXXXXXXXVOLTS 208/230  
PH 1 HZ 60

MINIMUM CIRCUIT AMPACITY	18.0	AMPS
OVERCURRENT PROTECTIVE DEVICE	USA	CANADA
MAX FUSE / BREAKER (HACR)	25	25
HFC - 410A	7 LBS. 14 OZ. OR	3.57 kg(SI)

10 +/- 3 °F DESIGN SUBCOOLING  
 Climatuff Duratuff Spine Fin Quick-Sess

**TRANE**

HEATING AND COOLING EQUIPMENT

A BUSINESS OF INGERSOLL RAND  
TYLER, TX 75707 ASSEMBLED IN USA

Intertek

3059934

COMPR. MOT.	12.4	RLA	208/230	V	10.2	LRA
O.D MOT.	2.80	FLA	208/230	V	1/3	HP
DESIGN PSI - HIGH 480 LOW 480						F. ID. XXX

**AHRI CERTIFIED™**  
[www.ahridirectory.org](http://www.ahridirectory.org)

Unitary Small AC  
 AHRI Standard 210/240

Certification applies only when the complete system is listed with AHRI.

**BARCODE**