

**TRANE XLi**MFR  
DATE 6/2023

MOD. NO. <b>4TTX7036E1000AA</b>	VOLTS	<b>208/230</b>
SERIAL NO. <b>XXXXXXXXXX</b>	PH <b>1</b>	HZ <b>60</b>
MINIMUM CIRCUIT AMPACITY	<b>18.4</b>	AMPS
OVERCURRENT PROTECTIVE DEVICE	USA	CANADA
MAX FUSE / BREAKER (HACR)	<b>30</b>	<b>30</b>
<b>HFC - 410A</b>	<b>8 LBS. 12 OZ. OR</b>	<b>3.97 kg(SI)</b>

**9 °F SC (TXV) OR SEE SH CHART IN LITERATURE SCCR 5kA rms**  
 Climatuff Duratuff Spine Fin Quick-Sess

**TRANE**CONDENSING UNIT  
SA11679

Trane U.S. Inc.

TYLER, TX 75707

ASSEMBLED IN USA



OUTDOOR USE

COMPR. MOT.	<b>14.2</b>	RLA	<b>208/230 V</b>	<b>78.1</b>	LRA
O.D MOT.	<b>0.64</b>	FLA	<b>200/230 V</b>	<b>1/8</b>	HP
DESIGN PSI - HIGH	480	LOW	480	F. ID.	<b>XXX</b>

**AHRI CERTIFIED™**  
[www.ahridirectory.org](http://www.ahridirectory.org)

Unitary Small AC  
 AHRI Standard 210/240

Certification applies only when the complete system  
 is listed with AHRI.

C

**BARCODE**