

XR 13

MFR
DATE 7/2007

MOD.NO. 4TTR3042A1000AA	VOLTS	200/230
SERIAL NO. XXXXXXXXX	PH 1	HZ 60
MINIMUM CIRCUIT AMPACITY	21.0	AMPS
OVERCURRENT PROTECTIVE DEVICE	USA	CANADA
MIN FUSE / BREAKER (HACR)	30	30
MAX FUSE / BREAKER (HACR)	35	35
HCFC - 22	6 LBS. 13 OZ.	OR 3.09 kg(SI)
10 °F DESIGN SUBCOOLING		

Climatuff DuraTuff Spine Fin Quick - Sess

AMERICAN STANDARD INC.
MANUFACTURER OF TRANE AND AMERICAN STANDARD
TYLER, TX 75707



LIMITED SECTION OF
CENTRAL COOLING
AIR CONDITIONER
23MF OUTDOOR USE

ASSEMBLED IN USA

COMPR. MOT.	15.4	RLA	200/230 V	93.5	LRA
O.D MOT.	1.4	FLA	200/230 V	1/6	HP
M.E.A. NO.	154 - 06E		F. ID.	31N	
DESIGN PSI - HIGH 480 LOW 480					

BARCODE



ARI Standard 210/240TM
Unitary Heat Pump
ARI Standard
210/240 UAC

CERTIFICATION APPLIES ONLY
WHEN THE COMPLETE SYSTEM
IS LISTED WITH ARI