

HEAT PUMP

MFR
DATE 4/2012

MOD. NO. 4TWB3036B1000BA	VOLTS	208/230
SERIAL NO. XXXXXXXXXX	PH 1	HZ 60
MINIMUM CIRCUIT AMPACITY	18.0	AMPS
OVERCURRENT PROTECTIVE DEVICE	USA	CANADA
MAX FUSE / BREAKER (HACR)	30	30
HFC - 410A	7 LBS.	06 OZ. OR
8 +/- 3 °F DESIGN SUBCOOLING		3.34 kg(SI)

Climatuff DuraTuff Spine Fin Quick-Sess Weathertron

TRANE U.S. INC.

MANUFACTURER OF TRANE AND AMERICAN STANDARD
TYLER, TX 75707

ASSEMBLED IN USA



LISTED SECTION OF
HEAT PUMP

3059934 OUTDOOR USE

COMPR. MOT. 13.2	RLA	208/230 V	63	LRA
O.D MOT. 1.00	FLA	200/230 V	1/5	HP
M.E.A. NO.		F. ID. J4Q		

DESIGN PSI - HIGH 480 LOW 480

AHRI CERTIFIED™
www.ahridirectory.org

Unitary Small AC
AHRI Standard 210/240

Certification applies only when the complete system
is listed with AHRI.

BARCODE