

XR 15

MFR
DATE 11/2009

MOD.NO. 4TWR5042E1000AA	VOLTS	208/230
SERIAL NO. XXXXXXXXX	PH 1	HZ 60
MINIMUM CIRCUIT AMPACITY	27.0	AMPS
OVERCURRENT PROTECTIVE DEVICE	USA	CANADA

MAX FUSE / BREAKER (HACR) **45** **45**
HFC - **410A** **12** LBS. **01** OZ. OR **5.47** kg(SI)

10 °F DESIGN SUBCOOLING
Climatuff DuraTuff Spine Fin Quick - Sess Weatherton

TRANE U.S INC.

MANUFACTURER OF TRANE AND AMERICAN STANDARD



LISTED SECTION OF
HEAT PUMP

TYLER, TX 75707 ASSEMBLED IN USA

3059934 OUTDOOR USE

COMPR. MOT.	19.9	RLA	208/230 V	109	LRA
O.D MOT.	1.00	FLA	200/230 V	1/5	HP
M.E.A. NO.			F. ID. XXX		
DESIGN PSI - HIGH	480	LOW	480		



CERTIFICATION APPLIES ONLY
WHEN THE COMPLETE SYSTEM
IS LISTED WITH ARI

BARCODE